



The Ecoview® sunscreen fabrics are made in Germany from 100% Trevira CS. These fabrics combine outward visibility with excellent glare and heat control.

- Made of 100% Trevira CS with no PVC, Formaldehyde or Halogen.
- Inherently fire retardant, complies with the NZ Building Code fire requirements.
- 3% open fabrics providing high-level UV protection.
- Good outward visibility with excellent thermal and visual comfort level.
- Metal backed fabrics for better heat and glare control.

## Ecoview **Ecoview Metallic** Whisper Riverstone Met Pelican Met Antique Met Pottery Earth Solitaire Met Jasper Met Gravel Met Oxide Gunmetal Met Ink







## Ecoview FR Specifications

5531SP SP Commercial FR Interior Roller Blinds																			
NZGBC Green Star DAB NZv1.1 NZGBC Green Star INT NZv1.1							DAB NZv1.1 / INT NZv1.1 - Credit												
12.1B - Glare Control 20.3A - Responsible Build 21C & 21D - Sustainable F		11.1B – Glare Control 20.2A – Responsible Building Materials 21C & 21D – Sustainable Products						12.1B/ 11.1B		20.3A / 20.2A	21C , 21D / 21C, 21D							Points	
Masterspec Index 1226GO / 1226GT									1 Point		1 Point	Towards Schedule							bution
		Width (mm)	Price Category	Openness Factor (OF)	AS/NZ 1530.2 Flammability Index	Solar Properties			VLT %		PVC	Sustainable Products						Contril	
Fabric Name						As	Rs	Ts	<10	≥10	PVC Free	ISO 14001	OEKO-TEX	GREENGUARD	Global GreenTag	Low VOC	RoHS / Lead Free	100% Trevira CS	SP - Potential Contribution Points
Ecoview Blanc	Ф <b>®</b>	3000	3	3%	1	5	58	37		37	•		•		•			•	2
Ecoview Whisper	Ф <b>®</b>	3000	3	3%	1	7	58	35		34	•		•		•			•	2
Ecoview Riverstone	Φ⊛	3000	3	3%	1	28	46	26		15	•		•		•			•	2
Ecoview Earth	Ф <b>®</b>	3000	3	3%	1	35	41	24	9		•		•		•			•	3
Ecoview Solitaire	Ф <b>®</b>	3000	3	3%	1	37	38	25	9		•		•		•			•	
Ecoview Ammo	Ф <b>®</b>	3000	3	3%	1	43	35	22	6		•		•		•			•	
Ecoview Gunmetal	Ф <b>®</b>	3000	3	3%	1	45	34	21	5		•		•		•			•	
Ecoview Rook	Ф <b>®</b>	3000	3	3%	1	48	32	20	3		•		•		•			•	
Ecoview Met Pelican	Ф <b>®</b>	2850	4	3%	3	38	52	10		10	•		•		•			•	2
Ecoview Met Antique	Ф <b>®</b>	2850	4	3%	3	40	51	9	8		•		•		•			•	3
Ecoview Met Pottery	Ф <b>®</b>	2850	4	3%	3	42	50	8	6		•		•		•			•	
Ecoview Met Jasper	Ф <b>®</b>	2850	4	3%	3	44	48	8	5		•		•		•			•	
Ecoview Met Gravel	Ф <b>®</b>	2850	4	3%	3	44	49	7	4		•		•		•			•	
Ecoview Met Oxide	Φ⊛	2850	4	3%	3	45	49	6	3		•		•		•			•	
Ecoview Met Ink	Ф <b>®</b>	2850	4	3%	3	46	48	6	3		•		•		•			•	3













## Key



Fire retardant

Openness Factor - this factor measures the proportion of holes in a woven fabric. This parameter, together with other technical properties of the fabric, should be considered when determining the degree of visibility, heat and glare control that the

AS/NZ Methods for fire tests on building materials, 1530.2 components and structures. Part 2: Test for flammability of materials.

Solar Absorbance - the proportion of solar radiation (heat) absorbed by the fabric. **A low figure** means the fabric absorbs little solar energy.

Solar Reflectance - this factor measures how much solar radiation is reflected by the fabric. **A high percentage** means the fabric performs well at reflecting solar

Solar Transmittance - the proportion of solar energy (heat) transmitted through the fabric. A low percentage means the fabric performs well at reducing solar

Visual Light Transmittance - the percentage of visible light coming through the fabric, that can be seen by the naked eye. A low figure shows a very efficient

PVC Free Does not contain PVC.

ISO 14001 The ISO 14001 standard is the most important international standard specifying the requirements of and Environmental Management System (EMS). Companies who implemented the ISO 14001 standard cannot use any harmful substances in their products.

OEKO-TEX The STANDARD 100 by OEKO-TEX® is a worldwide independent testing and certification system for harmful substances in textile products.

GREEN- This programme certifies materials for low chemical emissions, based on independent scientific testing and ongoing monitoring.

Global A third party, green building product rating GreenTag and certification system, underpinned by rigorous scientific and Life Cycle Assessment (LCA) processes.

VOC Volatile Organic Compound - these are organic chemicals that have a high vapour pressure at ordinary room temperature. This causes a large number of molecules to evaporate and enter the surrounding air. A fabric that has been certified for Low VOC Emissions has no, or very low levels of, these chemicals.

RoHS / Restriction of Harmful Substances the RoHS directive issued by the EU aims to restrict the use of certain dangerous substances. Any RoHS compliant component is tested for the presence of Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent chromium (Hex-Cr), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) For Cadmium and Hexavalent chromium, there must be less than 0.01% of the substance. For Lead, PBB, and PBDE, there must be no more than 0.1% of the material. Any RoHS compliant component must have 100 ppm or less of mercury and the mercury must not have been intentionally added to the component.

Trevira CS is a high spec, eco-friendly type of man-made yarn, which is free of PVC, Halogen and Formaldehyde. It is inherently and permanently fire-retardant thanks to its molecular structure. It stands for textiles made of 100% flame retardant fibres and yarns by Trevira and their partners in the spinning and yarn finishing stages.

## NZGBC Green Star DAB NZv1.1 / INT NZv1.1 credit

Glare Control - this credit rewards it using internal blinds. The nominated SP Blinds fabrics have a VLT less than 10% and can contribute towards a point, provided all the design details are in accordance with the Technical

20.2A

Responsible Building Materials -1 point is available where 90% (by cost) of all permanent formwork, pipes, flooring, blinds and cables in a project

recognised product declaration;
• OR meet the GBCA's Best Practice

Guidelines for PVC.

21C, 21D / Sustainable Products - up to 3 points are available when a proportion of all materials used in the project meet transparency and sustainability requirements under the initiatives.



