



The Ecoview® range of fabric is a collection of eco-friendly PVC-free sunscreen fabrics. The collection covers a variety of fabrics offering one or more of the following qualities:

- Certified for low VOC emissions
- Metal-backed fabrics for better heat and glare control
- 3% openness factor for efficient glare control
- Open weave decorative fabrics for high visibility and a multitude of natural light
- Fabrics sourced from an ISO 14001 certified manufacturer.

# Specifications

Fabric Name	Fabric Width	Openness Factor	Fire Classification	NZGBC Green Star Points			Eco-Spec			Solar & Optical Properties				
				IEQ	MAT	IEQ	OEKO-TEX / CEITEC Tested	PVC Free	ISO 14001	VLT	Ts	Rs	As	Sc
				3	4	9								
Ecoview White	2400	14%	AS/NZS 1530 Part 2 Flammability Index: 1		•			•	•	-	50	48	2	-
Ecoview Grey	2400	14%			•			•	•	-	26	15	59	-
Ecoview Taupe	2400	14%			•			•	•	-	20	12	68	-
Ecoview Black	2400	14%			•			•	•	-	20	3	77	-
Ecoview Met Grey	2400	12%			•			•	•	19	19	54	27	-
Ecoview Met Taupe	2400	12%			•			•	•	18	18	55	27	-
Ecoview Met Black	2400	12%			•			•	•	19	19	46	35	-
Ecoview Polar	2400	3%			•			•	•	38	36	55	9	0.43
Ecoview Barley	2400	3%			•			•	•	29	30	48	22	0.45
Ecoview Iron	2400	3%			•	•		•	•	6	6	21	73	0.55
Ecoview Raven	2400	3%			•	•		•	•	3	3	12	85	0.59
Ecoview Nero	2400	3%			•	•		•	•	2	2	4	94	0.63
Ecoview Met Polar	2400	3%			•	•		•	•	3	5	61	34	0.38
Ecoview Met Barley	2400	3%			•	•		•	•	3	5	65	30	0.36
Ecoview Met Iron	2400	3%			•	•		•	•	2	3	63	34	0.37
Ecoview Met Raven	2400	3%			•	•		•	•	2	2	63	35	0.37
Ecoview Met Nero	2400	3%			•	•		•	•	2	2	55	43	0.40
Ecoview Met Ash	2400	3%			•	•	•	•	•	8	8	50	46	0.61
Ecoview Met Steel	2400	3%			•	•	•	•	•	8	10	45	45	0.65
Ecoview Met Espresso	2400	3%			•	•	•	•	•	7	10	43	47	0.66
Ecoview Met Onyx	2400	3%		•	•	•	•	•	2	6	47	47	0.62	
Ecoview Met Night	2400	3%		•	•	•	•	•	7	10	43	47	0.66	
Ecoview Siberia	3000	n/a	Not Tested		•			•		-	-	-	-	-
Ecoview Sahara	3000	n/a			•			•		-	-	-	-	-
Ecoview Gobi	3000	n/a			•			•		-	-	-	-	-
Ecoview Piha	3000	n/a			•			•		-	-	-	-	-
Ecoview Pistachio	3000	n/a			•			•		-	-	-	-	-

# Key

- VLT** Visual Light Transmittance – the percentage of visible light coming through the fabric, that can be seen by the naked eye. A low figure shows a very efficient fabric.
- Ts** Solar Transmittance – the proportion of solar energy (heat) transmitted through the fabric. A low percentage means the fabric performs well at reducing solar energy.
- Rs** Solar Reflectance – this factor measures how much solar radiation is reflected by the fabric. A high percentage means the fabric performs well at reflecting solar energy.
- As** Solar Absorbance – the proportion of solar radiation (heat) absorbed by the fabric. A low figure means the fabric absorbs little solar energy.
- Sc** Shading Coefficient – shows how effective a fabric is at filtering the heat from solar radiation. It is expressed in a figure between 0 and 1. A low figure means high protection from heat.

**IEQ 3** This product may qualify for point(s) under this Green Star Credit (low VOC) in the Office Interiors 2009 tool.

**IEQ 9** This credit rewards daylight glare control using internal blinds. The nominated SP Blinds fabrics have a VLT less than 10 and can contribute towards a point, provided all the design details are in accordance with the Technical Manual.

**MAT 4** This credit rewards the reduction of PVC use in buildings. The nominated SP Blinds fabrics are PVC Free and assist the overall reduction calculation as it does not add to the PVC cost in the 'Actual PVC cost' column of the reference case.

