



## View<sup>®</sup> sunscreen fabric

Woven sunscreen fabrics combine outward visibility with day-time privacy. Providing excellent light and heat control, these fabrics offer a suitable solution for any environment and protection level needed based on the fabric's openness factor and colour.

- Made with Fiberglass core yarn or DOW ECOLIBRIUM bio-based plasticizers.
- Highly fire retardant (tested to AS/NZ Part II and/or III with a flammability Index under 12).
- Tested and certified for low VOC emissions - no chemicals harmful to the health or safety of users.
- 5% or 10% openness factor.
- UV Blockage - up to 96% (depending on colour).
- Dark colours have a VLT (Visual Light Transmittance) <10.
- Good outward visibility.



Cloud




Merino



Haze



Dolphin



Lemur



Roan



Bark



Rhino



Slate



Moonlight



Vanilla



Mist



Fudge



Char



Kudu




Chamois



Tahr



Sable



Oryx

5530SP SP Residential Interior Roller Blinds																					
Fabric Name	Width (mm)	Price Category	Openness Factor (OF)	AS/NZ 1530.3 Fire Classifications	Solar Properties			VLT %		PVC Free	Sustainable Products						Suitable for Moist Conditions	Indent Fabric	Matching Fabric*	Care Instructions**	
					As	Rs	Ts	<10	≥10		Global GreenTag	ISO 14001	OEKO-TEX	GREENGUARD	Low VOC	RoHS / Lead Free					100% Trevira CS
SP View Cloud	3100	2	5%	•	10	71	19		16					•	•	•		•			A
SP View Merino	3100	2	5%	•	18	61	21		18					•	•	•		•			A
SP View Haze	3100	2	5%	•	33	52	15		12					•	•	•		•			A
SP View Dolphin	3100	2	5%	•	57	33	10	7						•	•	•		•			A
SP View Lemur	3100	2	5%	•	80	14	6	5						•	•	•		•			A
SP View Roan	3100	2	5%	•	78	16	6	5						•	•	•		•			A
SP View Bark	3100	2	5%	•	81	13	6	5						•	•	•		•			A
SP View Rhino	3100	2	5%	•	83	12	5	5						•	•	•		•			A
SP View Slate	3100	2	5%	•	86	8	6	5						•	•	•		•			A
SP View Moonlight	3100	2	5%	•	9	71	20		17						•	•		•			A
SP View Vanilla	3100	2	5%	•	18	62	20		16						•	•		•			A
SP View Mist	3100	2	5%	•	37	51	12	9							•	•		•			A
SP View Fudge	3100	2	5%	•	87	6	7	7							•	•		•			A
SP View Char	3100	2	5%	•	90	6	4	4							•	•		•			A
SP View Kudu	3200	2	10%	•	25	58	17		22					•	•	•		•			A
SP View Chamois	3200	2	10%	•	35	50	15		20					•	•	•		•			A
SP View Tahr	3200	2	10%	•	77	11	12		17					•	•	•		•			A
SP View Sable	3000	2	5%		76	12	11		10						•	•		•			A
SP View Oryx	3000	2	5%		83	5	12		12						•	•		•			A

**OF** **Openness Factor** – this factor measures the proportion of holes in a woven fabric. This parameter, together with other technical properties of the fabric, should be considered when determining the degree of visibility, heat and glare control that the fabric offers.

**AS/NZ 1530.3** Methods for fire tests on building materials, components and structures. Part 3: Test for simultaneous determination of ignitability, flame propagation, heat release and smoke release.

**As** **Solar Absorbance** – the proportion of solar radiation (heat) absorbed by the fabric. **A low figure** means the fabric absorbs little solar energy.

**Rs** **Solar Reflectance** – this factor measures how much solar radiation is reflected by the fabric. **A high percentage** means the fabric performs well at reflecting solar energy.

**Ts** **Solar Transmittance** – the proportion of solar energy (heat) transmitted through the fabric. **A low percentage** means the fabric performs well at reducing solar energy.

**VLT%** **Visual Light Transmittance** – the percentage of visible light coming through the fabric, that can be seen by the naked eye. **A low figure** shows a very efficient fabric.

**PVC Free** Does not contain PVC.

**ISO 14001** The ISO 14001 standard is the most important international standard specifying the requirements of and Environmental Management System (EMS). Companies who implemented the ISO 14001 standard cannot use any harmful substances in their products.

**OEKO-TEX** The STANDARD 100 by OEKO-TEX® is a worldwide independent testing and certification system for harmful substances in textile products.

**GREENGUARD** This programme certifies materials for low chemical emissions, based on independent scientific testing and ongoing monitoring.

**Global GreenTag** A third party, green building product rating and certification system, underpinned by rigorous scientific and Life Cycle Assessment (LCA) processes.

**VOC** **Volatile Organic Compound** – these are organic chemicals that have a high vapour pressure at ordinary room temperature. This causes a large number of molecules to evaporate and enter the surrounding air. A fabric that has been certified for Low VOC Emissions has no, or very low levels of, these chemicals.

**RoHS / Lead Free** **Restriction of Harmful Substances** – the RoHS directive issued by the EU aims to restrict the use of certain dangerous substances. Any RoHS compliant component is tested for the presence of Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent chromium (Hex-Cr), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE). For Cadmium and Hexavalent chromium, there must be less than 0.01% of the substance. For Lead, PBB, and PBDE, there must be no more than 0.1% of the material. Any RoHS compliant component must have 100 ppm or less of mercury and the mercury must not have been intentionally added to the component.

**Trevira CS** Trevira CS is a high spec, eco-friendly type of man-made yarn, which is free of PVC, Halogen and Formaldehyde. It is inherently and permanently fire-retardant thanks to its molecular structure. It stands for textiles made of 100% flame retardant fibres and yarns by Trevira and their partners in the spinning and yarn finishing stages.



## Décorview<sup>®</sup> sunscreen fabric

---

Décorview sunscreen fabrics combine outward visibility daytime privacy. A variety of textures and openness factors add interest and versatility to the interior space.

- Made from PVC coated polyester.
- Fire retardant (selected fabrics).
- Fabrics offer between 5% to 6% openness – with the open weaves offering the best outward visibility levels for maximising view.
- UV block up to 96% (depending on colour).
- Durable and easy to clean.



Dove



Luna



Seafoam



Chestnut



Crow



Obsidian



Oyster



Frost



Rock



Granite

5530SP SP Residential Interior Roller Blinds																				
Fabric Name	Width (mm)	Price Category	Openness Factor (OF)	AS/NZ 1530.3 Fire Classifications	Solar Properties			VLT %		PVC		Sustainable Products					Suitable for Moist Conditions	Indent Fabric	Matching Fabric*	Care Instructions**
					As	Rs	Ts	<10	≥10	PVC Free	Global GreenTag	ISO 14001	OEKO-TEX	GREENGUARD	Low VOC	RoHS / Lead Free				
Décorview Dove	3000	3	6%		11	63	26		25							•			A	
Décorview Luna	3000	3	6%		25	50	25		23							•			A	
Décorview Seafog	3000	3	6%		30	47	23		22							•			A	
Décorview Chestnut	3000	3	6%		89	4	7		11							•			A	
Décorview Crow	3000	3	6%		79	11	10		13							•			A	
Décorview Obsidian	3000	3	6%		88	4	8		12							•			A	
Décorview Oyster	2500	4	5%		25	61	14		12							•	•		A	
Décorview Frost	2500	4	5%		38	49	13		12							•	•		A	
Décorview Rock	2500	4	5%		57	33	10	9								•	•		A	
Décorview Granite	2500	4	5%		82	11	7	6								•	•		A	

**OF** **Openness Factor** – this factor measures the proportion of holes in a woven fabric. This parameter, together with other technical properties of the fabric, should be considered when determining the degree of visibility, heat and glare control that the fabric offers.

**AS/NZ 1530.3** Methods for fire tests on building materials, components and structures. Part 3: Test for simultaneous determination of ignitability, flame propagation, heat release and smoke release.

**As** **Solar Absorbance** – the proportion of solar radiation (heat) absorbed by the fabric. **A low figure** means the fabric absorbs little solar energy.

**Rs** **Solar Reflectance** – this factor measures how much solar radiation is reflected by the fabric. **A high percentage** means the fabric performs well at reflecting solar energy.

**Ts** **Solar Transmittance** – the proportion of solar energy (heat) transmitted through the fabric. **A low percentage** means the fabric performs well at reducing solar energy.

**VLT%** **Visual Light Transmittance** – the percentage of visible light coming through the fabric, that can be seen by the naked eye. **A low figure** shows a very efficient fabric.

**PVC Free** Does not contain PVC.

**ISO 14001** The ISO 14001 standard is the most important international standard specifying the requirements of and Environmental Management System (EMS). Companies who implemented the ISO 14001 standard cannot use any harmful substances in their products.

**OEKO-TEX** The STANDARD 100 by OEKO-TEX® is a worldwide independent testing and certification system for harmful substances in textile products.

**GREENGUARD** This programme certifies materials for low chemical emissions, based on independent scientific testing and ongoing monitoring.

**Global GreenTag** A third party, green building product rating and certification system, underpinned by rigorous scientific and Life Cycle Assessment (LCA) processes.

**VOC** **Volatile Organic Compound** – these are organic chemicals that have a high vapour pressure at ordinary room temperature. This causes a large number of molecules to evaporate and enter the surrounding air. A fabric that has been certified for Low VOC Emissions has no, or very low levels of, these chemicals.

**RoHS / Lead Free** **Restriction of Harmful Substances** – the RoHS directive issued by the EU aims to restrict the use of certain dangerous substances. Any RoHS compliant component is tested for the presence of Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent chromium (Hex-Cr), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE). For Cadmium and Hexavalent chromium, there must be less than 0.01% of the substance. For Lead, PBB, and PBDE, there must be no more than 0.1% of the material. Any RoHS compliant component must have 100 ppm or less of mercury and the mercury must not have been intentionally added to the component.

**Trevira CS** Trevira CS is a high spec, eco-friendly type of man-made yarn, which is free of PVC, Halogen and Formaldehyde. It is inherently and permanently fire-retardant thanks to its molecular structure. It stands for textiles made of 100% flame retardant fibres and yarns by Trevira and their partners in the spinning and yarn finishing stages.