SP Blinds
creative light control







Thermo Block® Inspire blockout fabric

Blockout fabrics are designed to provide 100% light block making them the ultimate solution for any interior that requires darkness, such as bedrooms or AV rooms.
The Thermo Block® range also has the added benefit of providing insulating qualities.

- Made of 100% Polyester with no PVC.
- 100% blockout coating.


Dunstan


Aviemore


Tarawera


Taupo


Monowai


Wakatipu


Ellesmere


Pukaki


Rotoiti


McKerrow


Rotorua

Button

Angel


Enoki


Porcini


Portobello



Fawn


Morel


Truffle

Orlov

Highland


Caspian


Mustang


Norman


Friesian

Thermo Block® Inspire specifications

Oct. 2026

5530SP SP Residential Interior Roller Blinds - Blockout

masterspec Index - Interiors

Fabric Name	Width (mm)	Price Category	Openness Factor(OF)	Solar Properties				VLT %		PVC	Recyclable Products							Suitable for Moist Conditions	Indent Fabric	Matching Fabric*	Care Instructions**
				AS/NZ 1530.3 Flammability Index	As	Rs	Ts	< 10	≥ 10	PVC free	Global GreenTag	OKEO-TEK	GREENGUARD	Low VOC	RoHS / Lead Free	100% Trevira CS				
Thermo Block Dunstan	3000	2	Blockout	•				N/A		•			•	•	•					C
Thermo Block Aviemore	3000	3		•						•			•	•	•					C
Thermo Block Tarawera	3000	2		•						•			•	•	•					C
Thermo Block Taupo	3000	3		•						•			•	•	•					C
Thermo Block Monowai	3000	3		•						•			•	•	•					C
Thermo Block Wakatipu	3000	3		•						•			•	•	•					C
Thermo Block Ellesmere	3000	3		•						•			•	•	•					C
Thermo Block Pukaki	3000	3		•						•			•	•	•					C
Thermo Block Rotoiti	3000	3		•						•			•	•	•					C
Thermo Block McKerrow	3000	3		•						•			•	•	•					C
Thermo Block Rotorua	3000	3		•						•			•	•	•					C
Thermo Block Button	3000	2		•						•									•	C
Thermo Block Angel	3000	2		•						•									•	C
Thermo Block Enoki	3000	2		•						•									•	C
Thermo Block Porcini	3000	2		•						•									•	C
Thermo Block Portobello	3000	2		•						•									•	C
Thermo Block Fawn	3000	2		•						•									•	C
Thermo Block Morel	3000	2		•						•									•	C
Thermo Block Truffle	3000	2		•						•									•	C
Thermo Block Orlov	3000	4		•	26	74	0			•				•	•				•		C
Thermo Block Highland	3000	4		•	25	75	0			•				•	•				•		C
Thermo Block Caspian	3000	4		•	26	74	0			•				•	•				•		C
Thermo Block Mustang	3000	4		•	28	72	0			•				•	•				•		C
Thermo Block Norman	3000	4		•	26	74	0			•				•	•				•		C
Thermo Block Friesian	3000	4		•	28	72	0			•				•	•				•		C

*Matching fabric names are listed on the back of applicable fabric swatches.

**Care instructions are explained in the SP Blinds price list booklet

Thermo Block® is a registered trademark of SP Blinds Ltd.

Key to swatch label icons

- Eco friendly
- Fire retardant
- Suitable for moist conditions
- Indent fabric

Key to Specifications

OF	**Openness Factor** – this factor measures the proportion of holes in a woven fabric. This parameter, together with other technical properties of the fabric, should be considered when determining the degree of visibility, heat and glare control that the fabric offers.
AS/NZ 1530.3	**Methods for Fire Tests** on Building Materials, Components and Structures. Part 2: Test for Flammability of Materials
As	**Solar Absorbance** – the proportion of solar radiation (heat) absorbed by the fabric. **A low figure** means the fabric absorbs little solar energy.
Rs	**Solar Reflectance** – this factor measures how much solar radiation is reflected by the fabric. **A high percentage** means the fabric performs well at reflecting solar energy.
Ts	**Solar Transmittance** – the proportion of solar energy (heat) transmitted through the fabric. **A low percentage** means the fabric performs well at reducing solar energy.
PVC free	**Do not contain PVC**.
GREENGUARD	This programme certifies materials for low chemical emissions, based on independent scientific testing and ongoing monitoring.
VOC	**Voletile Organic Compound** – these are organic chemicals that have a high vapour pressure at ordinary room temperature. This causes a large number of molecules to evaporate and enter the surrounding air. A fabric that has been certified for Low VOC Emissions has no, or very low levels of these chemicals.
RoHS / Lead free	**Restriction of Harmful Substances** – the RoHS directive issued by the EU aims to restrict the use of certain dangerous substances. Any RoHS compliant component is tested for the presence of Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent chromium (Hex-Cr), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE). For Cadmium and Hexavalent chromium, there must be less than 0.01% of the substance. For Lead, PBB, and PBDE, there must be no more than 0.1% of the material. Any RoHS compliant component must have 100 ppm or less of mercury and the mercury must not have been intentionally added to the component.