SP Blinds

creative light control







View® sunscreen fabric

Woven sunscreen fabrics combine outward visibility with day-time privacy. Providing excellent light and heat control, these fabrics offer a suitable solution for any environment and protection level needed based on the fabric's openness factor and colour.

- Made with Fiberglass core yarn or DOW ECOLIBRIUM bio-based plasticizers.
- Highly fire retardant (tested to AS/NZ Part II and/or III with a flammability Index under 12).
- Tested and certified for low VOC emissions – no chemicals harmful to the health or safety of users.
- 5% to 10% openness factor
- UV Blockage – up to 96% (depending on colour).
- Dark colours have a VLT (Visual Light Transmittance) <10.
- Good outward visibility.

Snow

Platinum

Limestone



Chrome



Henna



Seal



Moonlight



Vanilla



Mist



Fudge



Char



Ice



Kudu



Chamois



Tahr



Oryx



Carbon

View® specifications

Oct. 2026

5530SP SP Residential Interior Roller Blinds - Sunscreen

masterspec Index - Interiors

Fabric Name	Width (mm)	Price Category	Openness Factor(OF)	Solar Properties: AS/NZ 1530.3 Flammability Index	Solar Properties: As	Solar Properties: Rs	Solar Properties: Ts	VLT %: < 10	VLT %: ≥ 10	PVC able Products: PVC free	Global GreenTag	OKEO-TEK	GREENGUARD	Low VOC	RoHS / Lead Free	100% Trevira CS	Suitable for Moist Conditions	Indent Fabric	Matching Fabric*	Care Instructions**
SP View Snow	3000	2	7%	•	14	62	24		20				•				•			A
SP View Platinum	3000	2	5-8%	•	14	70	16		14				•				•			A
Sp View Limestone	3000	2	5-8%	•	17	56	27		25				•				•			A
SP View Chrome	3000	2	5%	•	36	49	15		11				•				•			A
SP View Henna	3000	2	6%	•	55	30	15		11				•				•			A
SP View Seal	3000	2	8%	•	83	8	9	8					•				•			A
SP View Moonlight	3100	2	5%	•	9	71	20		17					•	•		•			A
SP View Vanilla	2500	2	5%	•	18	62	20		16					•	•		•			A
SP View Mist	3100	2	5%	•	37	51	12	9						•	•		•			A
SP View Fudge	3100	2	5%	•	87	6	7	7						•	•		•			A
SP View Char	3100	2	5%	•	90	6	4	4						•	•		•			A
SP View Ice	3000	2	10%	•	12	63	25		20				•	•	•		•			A
SP View Kudu	3000	2	10%	•	25	58	17		22				•	•	•		•			A
SP View Chamois	3000	2	10%	•	35	50	15		20				•	•	•		•			A
SP View Tahr	3000	2	10%	•	77	11	12		17				•	•	•		•			A
SP View Oryx	3000	2	10%	•	83	5	12		12				•	•	•		•			A
SP View Carbon	3000	2	10%	•	85	3	12		12				•	•	•		•			A

*Matching fabric names are listed on the back of applicable fabric swatches.

**Care instructions are explained in the SP Blinds price list booklet

View® is a registered trademark of SP Blinds Ltd.

Key to swatch label icons

- Eco friendly
- Fire retardant
- Suitable for moist conditions
- Indent fabric

Key to Specifications

OF – **Openness Factor** – this factor measures the proportion of holes in a woven fabric. This parameter, together with other technical properties of the fabric, should be considered when determining the degree of visibility, heat and glare control that the fabric offers.

AS/NZ 1530.3 – **Methods for Fire Tests** on Building Materials, Components and Structures. Part 2: Test for Flammability of Materials

As – **Solar Absorbance** – the proportion of solar radiation (heat) absorbed by the fabric. **A low figure** means the fabric absorbs little solar energy.

Rs – **Solar Reflectance** – this factor measures how much solar radiation is reflected by the fabric. **A high percentage** means the fabric performs well at reflecting solar energy.

Ts – **Solar Transmittance** – the proportion of solar energy (heat) transmitted through the fabric. **A low percentage** means the fabric performs well at reducing solar energy.

VLT % – **Visual Light Transmittance** – the percentage of visible light coming through the fabric, that can be seen by the naked eye. **A low figure** shows a very efficient fabric.

PVC free – **Do not contain PVC.**

GREENGUARD – This programme certifies materials for low chemical emissions, based on independent scientific testing and ongoing monitoring.

VOC – **Voletile Organic Compound** – these are organic chemicals that have a high vapour pressure at ordinary room temperature. This causes a large number of molecules to evaporate and enter the surrounding air. A fabric that has been certified for Low VOC Emissions has no, or very low levels of these chemicals.

RoHS / Lead free – **Restriction of Harmful Substances** – the RoHS directive issued by the EU aims to restrict the use of certain dangerous substances. Any RoHS compliant component is tested for the presence of Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent chromium (Hex-Cr), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE). For Cadmium and Hexavalent chromium, there must be less than 0.01% of the substance. For Lead, PBB, and PBDE, there must be no more than 0.1% of the material. Any RoHS compliant component must have 100 ppm or less of mercury and the mercury must not have been intentionally added to the component.

SP Blinds

creative light control







Décorview® sunscreen fabric

Décorview sunscreen fabrics combine outward visibility daytime privacy. A variety of textures and openness factors add interest and versatility to the interior space.

- Made from PVC coated polyester.
- Fire retardant (selected fabrics).
- Fabrics with 6% to 8% openness feature open weaves that provide excellent outward visibility, making them ideal for maximising views
- UV block up to 96% (depending on colour).
- Durable and easy to clean.



Dove



Luna



Seafog



Chestnut



Crow



Obsidian



Rice



Chia



Maize



Sesame

Décorview® specifications

Oct. 2026

5530SP SP Residential Interior Roller Blinds - Sunscreen

masterspec Index - Interiors

Fabric Name	Width (mm)	Price Category	Openness Factor(OF)	Solar Properties: AS/NZ 1530.3 Flammability Index	Solar Properties: As	Solar Properties: Rs	Solar Properties: Ts	VLT %: < 10	VLT %: ≥ 10	PVC able Products: PVC free	Global GreenTag	OKEO-TEK	GREENGUARD	Low VOC	RoHS / Lead Free	100% Trevira CS	Suitable for Moist Conditions	Indent Fabric	Matching Fabric*	Care Instructions**
Décorview Dove	3000	3	6%		11	63	26		25					•			•			A
Décorview Luna	3000	3	6%		25	50	25		23					•			•			A
Décorview Seafog	3000	3	6%		30	47	23		22					•			•			A
Décorview Chestnut	3000	3	6%		89	4	7		11					•			•			A
Décorview Crow	3000	3	6%		79	11	10		13					•			•			A
Décorview Obsidian	3000	3	6%		88	4	8		12					•			•			A
Décor View Rice	2800	4	8%									•								A
Décor View Chia	2800	4	8%									•								A
Décor View Maize	2800	4	8%									•								A
Décor View Sesame	2800	4	8%									•								A

*Matching fabric names are listed on the back of applicable fabric swatches.

**Care instructions are explained in the SP Blinds price list booklet

View® is a registered trademark of SP Blinds Ltd.

Key to swatch label icons

Eco friendly
Fire retardant
Suitable for moist conditions
Indent fabric

Key to Specifications

OF	**Openness Factor** – this factor measures the proportion of holes in a woven fabric. This parameter, together with other technical properties of the fabric, should be considered when determining the degree of visibility, heat and glare control that the fabric offers.
AS/NZ 1530.3	**Methods for Fire Tests** on Building Materials, Components and Structures. Part 2: Test for Flammability of Materials
As	**Solar Absorbance** – the proportion of solar radiation (heat) absorbed by the fabric. **A low figure** means the fabric absorbs little solar energy.
Rs	**Solar Reflectance** – this factor measures how much solar radiation is reflected by the fabric. **A high percentage** means the fabric performs well at reflecting solar energy.
Ts	**Solar Transmittance** – the proportion of solar energy (heat) transmitted through the fabric. **A low percentage** means the fabric performs well at reducing solar energy.
VLT %	**Visual Light Transmittance** – the percentage of visible light coming through the fabric, that can be seen by the naked eye. **A low figure** shows a very efficient fabric.
PVC free	**Do not contain PVC**.
GREENGUARD	This programme certifies materials for low chemical emissions, based on independent scientific testing and ongoing monitoring.
VOC	**Voletile Organic Compound** – these are organic chemicals that have a high vapour pressure at ordinary room temperature. This causes a large number of molecules to evaporate and enter the surrounding air. A fabric that has been certified for Low VOC Emissions has no, or very low levels of these chemicals.
RoHS / Lead free	**Restriction of Harmful Substances** – the RoHS directive issued by the EU aims to restrict the use of certain dangerous substances. Any RoHS compliant component is tested for the presence of Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent chromium (Hex-Cr), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE). For Cadmium and Hexavalent chromium, there must be less than 0.01% of the substance. For Lead, PBB, and PBDE, there must be no more than 0.1% of the material. Any RoHS compliant component must have 100 ppm or less of mercury and the mercury must not have been intentionally added to the component.